

# Nutmeg Pavers



 **COROBRIK<sup>®</sup>**



# Nutmeg Pavers

- Comprises a blend of brownish red and blue hues.
- Ideal for vehicular traffic applications. The products inherent properties and aesthetic characteristics mask the existence of tyre marks and oil stains.
- Ideal for definition and design work when used in conjunction with Cederberg pavers.



## Technical Information for Nutmeg Pavers

PRODUCT	SABS Classification	Dimensions (mm)	Quantity/m <sup>2</sup> with 3mm Flexible Joints	Average Mass (kg)	Average Modulus of Rupture (MPa)	Typical 24hr Cold Water Absorption Ave (%)
Nutmeg Pavers	PA	220 x 108.5 x 50	41	2.6	5.4	6
		200 x 98.5 x 60	48.5	2.5	5.3	5.6

\*The 60mm thick pavers typically have Modulus of Ruptures values in compliance with SABS PA Classification. 60mm thick pavers have been evaluated by Ninham Shand Consulting Engineers and can be expected to perform in 3.0 MESA (E2 Traffic Class) loading applications.

Every effort has been made in the photographic, reproduction and printing process to feature a portrayal of each panel as it would appear in real life. However, the only accurate way to assess the true aesthetic appeal of face brick is to view the product.